

uniK 05+

Professional Active Reference 5" Studio Monitor



The uniK 05+ is the result of extensive development work performed in Germany, defining a new quality level in its class. With its new 5" kevlar low frequency driver and a new custom engineered and powerful high frequency magnetostatic tweeter, the uniK 05+ offers many improvements over our successful uniK 05 and will easily become an important part of your studio setup with its clear and strong sound image.

What makes uniK 05+ unique?

The uniK 05+ studio monitor offers true full range quality with extended low end in a small case and an entirely new signal processing and amplifier unit with a perfect order low-z and low noise design. Mos-Fet Bi-amplification ensures a high slew-rate and fast setting, featuring true analog vintage sound processing with LC-like gyrator technology for a stressless and silky sound.

A completely new feature is the unique one knob sound character adjustment from smooth to bright, allowing you to change parameters for every room and preference. The additional high resolution High and Low switches add additional control. And of course the uniK 05+ studio monitor features a real precision gain attenuator, instead of a simple volume control.

The new design of the crossover ensures an excellent phase response and safe power limitation, driving the woofer and tweeter in phase for optimal step response. The tweeter features a newly upgraded magnetostatic design with extremely low moving mass for extended frequency and fast transient response and high sound resolution. The matching woofer consists of a kevlar composite cone with high stiffness ensuring better piston motion and excellent low-end sound reproduction.

Another new feature is the flexible rubber feet with discrete height adjustment. They are not only helpful to reduce unwanted vibrations, but also allow you to tilt the speaker towards the precise listening point - a great feature for typical near field applications.

Other new special features that are not standard in this class are standby to save power

ROOM ADJUSTMENTS



SIDE - TILT UP



SIDE - TILT DOWN



Features

- Biamp 2-Way Powered Speaker System
- Active Studio Monitor Speaker
- HF Driver: extremely low mass magnetostatic tweeter $\Phi 49 \times 26$ mm
- LF Driver: 5" kevlar curved cone (magnetic shielding type)
- Output Power: 80W (HF: 40W, LF: 40W), 110W AC consumption power
- Frequency Response: 49Hz - 25kHz
- Input Impedance: 27.2kOhm (balanced) / 13.6kOhm (unbalanced)
- Crossover Point: 3.2kHz
- SPL: 101dB, Peak 104dB
- Input Connectors: XLR / TRS 1/4" combo connector, balanced / unbalanced
- Gain Control: -14 .. 0dB .. +14
- Room Adjustments Control: Character: -6 .. 0dB .. +6; Low: -5 .. 0dB .. +5; High: -5 .. 0dB .. +5
- Rear Bass-Reflex ventilation, optimized for near field application
- Ground lift switch
- Standby function, can be turned on and off
- Indicator: multi color LED on front panel, power on orange, standby red
- Feet: 4 pieces rubberized, adjustable height separately
- Working Voltage: AC100-240V 50/60Hz
- Dimensions (W x H x D): 190 x 265 x 210mm
- Weight: 4.4 kg

BACK



uniK 05+

Professional Active Reference 5" Studio Monitor

consumption (can be disabled) and a ground lift switch.

And with its copper color woofer cone and the high quality matte cabinet finish, it looks quite *uniK*, too!

