

aktiv 08

High Performance 8" Studio Reference Monitor



Intended as successor for the popular nEar08 eXperience, the aktiv 08 studio near field reference monitor has been developed to offer the best 8" monitoring solution for the entry level.

With an extended low frequency response and a top quality kevlar 8" driver, our aktiv 08 delivers unparalleled punch in the low-mid frequency - a major improvement over the paper and polypropylene drivers used in many comparable products. Compared to the previous generation, the aktiv 08 is build with a new tuning by our engineers in Germany, a higher quality silk dome tweeter and it also integrates a completely new design of the crossover circuitry. This gives aktiv 08 the pole position in the area of professional level studio monitoring if you are on a budget and won't accept a compromise on quality and sound.

All this makes aktiv 08 the perfect alternative to our higher end uniK 08+ reference monitor if you are on a budget.

Features

- 2-way powered speaker / active studio monitor speaker
- 8" kevlar curved cone (magnetic shielding type) as LF driver
- 1" silk dome tweeter as HF driver
- output power 90W (HF 30W, LF 60W), 130W AC consumption power
- input connections: XLR / TS1/4" combo connector, balanced / unbalanced input
- input impedance: 23.3 kOhm balanced, 13.3 kOhm unbalanced
- input sensitivity: 130mV@1Watt, 1V@60Watt
- frequency response: 40Hz - 20kHz
- crossover frequency: 2 kHz
- SPL: 90dB +/- 3dB
- operating voltage: AC100-240V 50/60Hz, with 115V / 230V AC selection switch
- blue power LED on the front
- standby function, can be turned on and off (only models sold in certain countries)
- dimensions: 358 mm(H) x 255 mm(W) x 322 mm(D)
- weight: ca. 10.2kg

BACK

