

# nEar06

70 Watt Bi-Amplified 6" Studio Reference Monitors



nEar06 is designed to generate near perfect sonic reproduction. nEar06 not only inherits the fine audio quality of nEar05, but also has very bright sound quality and provides a better frequency response in the low range in comparison.

nEar06 offers stable and balanced low frequency response with defined mid to high frequency response. Both drivers are magnetically shielded for music production in computer environments. High current power amplifiers offer high sound pressure with very low non-linear distortion. nEar06 is an ideal solution for professional recording studios and home recording studios alike.

A perfect companion for nEar06 is our subwoofer SW10K.

## Features

- integral bi-amplified 70 Watt active near-field monitoring speaker
- 6" polypropylene curved cone low frequency driver
- 1" silk high frequency driver
- 1 balanced XLR input, 1 balanced/unbalanced 1/4" TRS input
- input sensibility: 270 mV
- input impedance: 20k Ohm symmetric, 10k Ohm unsymmetric
- Protection : RF interference, output current limiting, over temperature, turn-on/off
- frequency response: 55Hz - 20 kHz
- crossover frequency: 2.7 kHz
- low frequency amplifier: 40W
- high frequency amplifier: 30W
- blue power LED on the front
- curved front panel shape to optimize acoustic characteristics
- dimensions: 280mm (H) x 200mm (W) x 223mm (D)
- weight: ca. 7.5 / speaker

## BACK

