

uniK 05

Professional Active Reference 5" Studio Monitor



uniK 05 are the result of extensive development work done in Germany, to provide a professional active reference monitor that defines a new level of quality in this class. The monitor features a new 5" kevlar low frequency driver and a custom engineered and powerful high frequency ribbon tweeter with an extraordinary light membrane. This provides a very clear, strong and precise sound image especially in the high frequencies. With less moving mass compared to conventional tweeters, a new level of impulse response with minimized distortion is achieved. The optimized matching mechanical design of the uniK 05 cabinet provides a special and truly unique sound characteristic that makes this monitor an important part of your studio setup instantly.

Please note that this product has been replaced with the upgraded uniK 05+ model.

Features

- 2-Way Powered Speaker
- Active Studio Monitor Speaker
- ribbon tweeter 49 x 26 mm as HF driver
- 5" kevlar curved cone (magnetic shielding type) LF driver
- Output Power: 60W (HF: 30W, LF: 30W), 85W AC consumption power
- Frequency Response: 49Hz - 22kHz
- Input Impedance: 42kOhm (balanced) / 8.5kOhm (unbalanced)
- 2.5kHz Crossover Point
- SPL: 89dB ?3dB @1W / 1M at 300. 400. 500. 600 Hz
- Related Noise Power: 25W (THD=1%, 4ohm load, 1kHz)
- Input Sensitivity: 60mV@1W; 300mV@25W (500 Hz)
- XLR / TS 1/4" combo connector, balanced / unbalanced input
- min - 0dB - max volume control on back panel
- blue LED display (power)
- dimensions: 190 x 265 x 210mm
- weight: 4,28kg

BACK

