

uniK 08

Professional Active Reference 8" Studio Monitor



uniK 08 are the result of extensive development work done in Germany, to provide a professional active reference monitor that defines a new level of quality in this class. The monitor features a new 8" kevlar low frequency driver and a custom engineered and powerful high frequency ribbon tweeter with an extraordinary light membrane. This provides a very clear, strong and precise sound image especially in the high frequencies. With less moving mass compared to conventional tweeters, a new level of impulse response with minimized distortion is achieved. In combination with the optimized mechanical design of the cabinet, uniK 08 provides special and truly unique sound characteristics that allow this monitor to satisfy the highest demands in a professional studio environment.

Please note that this product has been replaced with the upgraded uniK 08+ model.

Features

- Biamp 2-Way Powered Speaker
- Active Studio Monitor Speaker
- ribbon tweeter 49 x 26 mm as HF driver
- 8" kevlar curved cone (magnetic shielding type) LF driver
- Output Power: 90W (HF: 30W, LF: 60W), 130W AC consumption power
- Frequency Response: 37Hz ? 22kHz
- Input Impedance: 42kOhm (balanced) / 8.5kOhm (unbalanced)
- 2.4kHz Crossover Point
- SPL: 90dB ?3dB @1W / 1M at 300. 400. 500. 600 Hz
- Related Noise Power: 45W (THD=1%, 4ohm load, 1kHz)
- Input Sensitivity: 75mV@1W; 485mV@45W (1 kHz)
- XLR / TS 1/4" combo connector, balanced / unbalanced input
- min - 0dB - max volume control on back panel
- blue LED display (power)
- dimensions: 252 x 352 x 319mm
- weight: 7,9kg

BACK

